



AT THE
ROOT OF
INDUSTRY

ABOUT US

Established in 1974 All India Hoses & Polymers is a professionally managed company, started business in 1974 with a motto to serve its customers with best quality products, prompt and efficient industrial services in the field of Hoses and Polymers.

We have always manufactured and supplied products which are the best available in the market with best services and quality, available at most priority.

BRANDS WE DEAL

Manufacturing production industry

www.allindiahosespolymers.in

INDEX

INDUSTRIAL & HYDRAULIC HOSES Page 1-66	HOSE CLAMPS Page 95-97
HYDRAULIC HOSES Page 67-68	GASKET SHEETS Page 98-111
HYDRAULIC HOSES Page 69	ASBESTOS PACKINGS & BRAKE LINERS Page 112-114
SS BELLOW HOSES Page 70-74	PTFE PACKINGS & TAPES Page 115-121
FLEXIBLE HOSES Page 75-80	ASBESTOS MILLBOARDS Page 122-123
PVC BRAIDED & SUCTON HOSES Page 81-86	ELECTRICAL INSULATING MATS Page 124
SILICON, PU & THINER HOSES Page 89-90	ELECTRICAL INSULATING MATS Page 125-126
COMPOSITE HOSES Page 91-94	RUBBER SHEETS Page 127

ABOUT US

Established in 1974 All India Hoses & Polymers is a professionally managed company, started business in 1974 with a motto to serve its customers with best quality products, prompt and efficient industrial services in the field of Hoses and Polymers.

We have always manufactured and supplied products which are the best available in the market with best services and quality, available at most priority.

BRANDS WE DEAL

Manufacturing production industry

www.allindiahosespolymers.in

INDEX

INDUSTRIAL & HYDRAULIC HOSES Page 1-66	HOSE CLAMPS Page 95-97
HYDRAULIC HOSES Page 67-68	GASKET SHEETS Page 98-111
HYDRAULIC HOSES Page 69	ASBESTOS PACKINGS & BRAKE LINERS Page 112-114
SS BELLOW HOSES Page 70-74	PTFE PACKINGS & TAPES Page 115-121
FLEXIBLE HOSES Page 75-80	ASBESTOS MILLBOARDS Page 122-123
PVC BRAIDED & SUCTON HOSES Page 81-86	ELECTRICAL INSULATING MATS Page 124
SILICON, PU & THINER HOSES Page 89-90	ELECTRICAL INSULATING MATS Page 125-126
COMPOSITE HOSES Page 91-94	RUBBER SHEETS Page 127

SAE 100 R1 AT

Size	Inner Dia	Outer Dia	Weight	Pressure	Temp	Length
1/2"	12.7	15.2	0.12	100	100	100
3/4"	19.0	21.5	0.18	100	100	100
1"	25.4	27.9	0.24	100	100	100
1 1/4"	31.8	34.3	0.30	100	100	100
1 1/2"	38.1	40.6	0.36	100	100	100
2"	50.8	53.3	0.48	100	100	100
2 1/2"	63.5	66.0	0.60	100	100	100
3"	76.2	78.7	0.72	100	100	100
3 1/2"	88.9	91.4	0.84	100	100	100
4"	101.6	104.1	0.96	100	100	100
4 1/2"	114.3	116.8	1.08	100	100	100
5"	127.0	129.5	1.20	100	100	100
5 1/2"	139.7	142.2	1.32	100	100	100
6"	152.4	154.9	1.44	100	100	100
6 1/2"	165.1	167.6	1.56	100	100	100
7"	177.8	180.3	1.68	100	100	100
7 1/2"	190.5	193.0	1.80	100	100	100
8"	203.2	205.7	1.92	100	100	100
8 1/2"	215.9	218.4	2.04	100	100	100
9"	228.6	231.1	2.16	100	100	100
9 1/2"	241.3	243.8	2.28	100	100	100
10"	254.0	256.5	2.40	100	100	100
10 1/2"	266.7	269.2	2.52	100	100	100
11"	279.4	281.9	2.64	100	100	100
11 1/2"	292.1	294.6	2.76	100	100	100
12"	304.8	307.3	2.88	100	100	100
12 1/2"	317.5	320.0	3.00	100	100	100
13"	330.2	332.7	3.12	100	100	100
13 1/2"	342.9	345.4	3.24	100	100	100
14"	355.6	358.1	3.36	100	100	100
14 1/2"	368.3	370.8	3.48	100	100	100
15"	381.0	383.5	3.60	100	100	100
15 1/2"	393.7	396.2	3.72	100	100	100
16"	406.4	408.9	3.84	100	100	100
16 1/2"	419.1	421.6	3.96	100	100	100
17"	431.8	434.3	4.08	100	100	100
17 1/2"	444.5	447.0	4.20	100	100	100
18"	457.2	459.7	4.32	100	100	100
18 1/2"	469.9	472.4	4.44	100	100	100
19"	482.6	485.1	4.56	100	100	100
19 1/2"	495.3	497.8	4.68	100	100	100
20"	508.0	510.5	4.80	100	100	100
20 1/2"	520.7	523.2	4.92	100	100	100
21"	533.4	535.9	5.04	100	100	100
21 1/2"	546.1	548.6	5.16	100	100	100
22"	558.8	561.3	5.28	100	100	100
22 1/2"	571.5	574.0	5.40	100	100	100
23"	584.2	586.7	5.52	100	100	100
23 1/2"	596.9	599.4	5.64	100	100	100
24"	609.6	612.1	5.76	100	100	100
24 1/2"	622.3	624.8	5.88	100	100	100
25"	635.0	637.5	6.00	100	100	100
25 1/2"	647.7	650.2	6.12	100	100	100
26"	660.4	662.9	6.24	100	100	100
26 1/2"	673.1	675.6	6.36	100	100	100
27"	685.8	688.3	6.48	100	100	100
27 1/2"	698.5	701.0	6.60	100	100	100
28"	711.2	713.7	6.72	100	100	100
28 1/2"	723.9	726.4	6.84	100	100	100
29"	736.6	739.1	6.96	100	100	100
29 1/2"	749.3	751.8	7.08	100	100	100
30"	762.0	764.5	7.20	100	100	100
30 1/2"	774.7	777.2	7.32	100	100	100
31"	787.4	789.9	7.44	100	100	100
31 1/2"	800.1	802.6	7.56	100	100	100
32"	812.8	815.3	7.68	100	100	100
32 1/2"	825.5	828.0	7.80	100	100	100
33"	838.2	840.7	7.92	100	100	100
33 1/2"	850.9	853.4	8.04	100	100	100
34"	863.6	866.1	8.16	100	100	100
34 1/2"	876.3	878.8	8.28	100	100	100
35"	889.0	891.5	8.40	100	100	100
35 1/2"	901.7	904.2	8.52	100	100	100
36"	914.4	916.9	8.64	100	100	100
36 1/2"	927.1	929.6	8.76	100	100	100
37"	939.8	942.3	8.88	100	100	100
37 1/2"	952.5	955.0	9.00	100	100	100
38"	965.2	967.7	9.12	100	100	100
38 1/2"	977.9	980.4	9.24	100	100	100
39"	990.6	993.1	9.36	100	100	100
39 1/2"	1003.3	1005.8	9.48	100	100	100
40"	1016.0	1018.5	9.60	100	100	100
40 1/2"	1028.7	1031.2	9.72	100	100	100
41"	1041.4	1043.9	9.84	100	100	100
41 1/2"	1054.1	1056.6	9.96	100	100	100
42"	1066.8	1069.3	10.08	100	100	100
42 1/2"	1079.5	1082.0	10.20	100	100	100
43"	1092.2	1094.7	10.32	100	100	100
43 1/2"	1104.9	1107.4	10.44	100	100	100
44"	1117.6	1120.1	10.56	100	100	100
44 1/2"	1130.3	1132.8	10.68	100	100	100
45"	1143.0	1145.5	10.80	100	100	100
45 1/2"	1155.7	1158.2	10.92	100	100	100
46"	1168.4	1170.9	11.04	100	100	100
46 1/2"	1181.1	1183.6	11.16	100	100	100
47"	1193.8	1196.3	11.28	100	100	100
47 1/2"	1206.5	1209.0	11.40	100	100	100
48"	1219.2	1221.7	11.52	100	100	100
48 1/2"	1231.9	1234.4	11.64	100	100	100
49"	1244.6	1247.1	11.76	100	100	100
49 1/2"	1257.3	1259.8	11.88	100	100	100
50"	1270.0	1272.5	12.00	100	100	100

SAE 100 R1 AT

CONSTRUCTION: High strength polyamide reinforcement.

WEAR: High resistance to abrasion.

TEMPERATURE: -40°C to +100°C.

APPLICATIONS: Hydraulic systems, power steering, etc.

SAE 100 R1 AT

Size	Inner Dia	Outer Dia	Weight	Pressure	Temp	Length
1/2"	12.7	15.2	0.12	100	100	100
3/4"	19.0	21.5	0.18	100	100	100
1"	25.4	27.9	0.24	100	100	100
1 1/4"	31.8	34.3	0.30	100	100	100
1 1/2"	38.1	40.6	0.36	100	100	100
2"	50.8	53.3	0.48	100	100	100
2 1/2"	63.5	66.0	0.60	100	100	100
3"	76.2	78.7	0.72	100	100	100
3 1/2"	88.9	91.4	0.84	100	100	100
4"	101.6	104.1	0.96	100	100	100
4 1/2"	114.3	116.8	1.08	100	100	100
5"	127.0	129.5	1.20	100	100	100
5 1/2"	139.7	142.2	1.32	100	100	100
6"	152.4	154.9	1.44	100	100	100
6 1/2"	165.1	167.6	1.56	100	100	100
7"	177.8	180.3	1.68	100	100	100
7 1/2"	190.5	193.0	1.80	100	100	100
8"	203.2	205.7	1.92	100	100	100
8 1/2"	215.9	218.4	2.04	100	100	100
9"	228.6	231.1	2.16	100	100	100
9 1/2"	241.3	243.8	2.28	100	100	100
10"	254.0	256.5	2.40	100	100	100
10 1/2"	266.7	269.2	2.52	100	100	100
11"	279.4	281.9	2.64	100	100	100
11 1/2"	292.1	294.6	2.76	100	100	100
12"	304.8	307.3	2.88	100	100	100
12 1/2"	317.5	320.0	3.00	100	100	100
13"	330.2	332.7	3.12	100	100	100
13 1/2"	342.9	345.4	3.24	100	100	100
14"	355.6	358.1	3.36	100	100	100
14 1/2"	368.3	370.8	3.48	100	100	100
15"	381.0	383.5	3.60	100	100	100
15 1/2"	393.7	396.2	3.72	100	100	100
16"	406.4	408.9	3.84	100	100	100
16 1/2"	419.1	421.6	3.96	100	100	100
17"	431.8	434.3	4.08	100	100	100
17 1/2"	444.5	447.0	4.20	100	100	100
18"	457.2	459.7	4.32	100	100	100
18 1/2"	469.9	472.4	4.44	100	100	100
19"	482.6	485.1	4.56	100	100	100
19 1/2"	495.3	497.8	4.68	100	100	100
20"	508.0	510.5	4.80	100	100	100
20 1/2"	520.7	523.2	4.92	100	100	100
21"	533.4	535.9	5.04	100	100	100
21 1/2"	546.1	548.6	5.16	100	100	100
22"	558.8	561.3	5.28	100	100	100
22 1/2"	571.5	574.0	5.40	100	100	100